

CERTIFICATE OF MAILING BY FIRST CLASS MAIL (37 CFR 1.8)

Applicant(s): Yasushi AKIYAMA et al.

Docket No.

2002JP311

Serial No. ·

10/519,242

Filing Date

December 22, 2004

Examiner


WU, Ives J.

Group Art Unit

1713

Invention: COMPOSITION FOR ANTIREFLECTIVE COATING AND METHOD FOR FORMING SAME

SEP 14 2005

I hereby certify that this English Language abstract of JP 05-088598 - 2 Pages

(Identify type of correspondence)

is being deposited with the United States Postal Service as first class mail in an envelope addressed to: The

Commissioner of Patents and Trademarks, Washington, D.C. 20231-0001 on September 14, 2005

(Date)

MARIA T. SANCHEZ

(Typed or Printed Name of Person Mailing Correspondence)


(Signature of Person Mailing Correspondence)

Note: Each paper must have its own certificate of mailing.

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 05-088598

(43)Date of publication of application : 09.04.1993

(51)Int.Cl. G03H 1/18

B23K 1/14

B41K 1/00

G03H 1/20

(21)Application number : 03-252619 (71)Applicant : TOPPAN PRINTING CO LTD

(22)Date of filing : 30.09.1991 (72)Inventor : HATTA SATOSHI

KOIDE YOSHIO


OKANO SHIGERU

(54) PRODUCTION OF MULTIFACED ORIGINAL PLATE FOR REPRODUCTION OF HOLOGRAM

(57)Abstract:

PURPOSE: To prevent the generation of defective transfer parts, spacings and groove traces to be generated in the case of press molding of hologram products and to allow relief patterns to be well transferred by eliminating the spacings and grooves generated between molds for duplicating the relief holograms.

CONSTITUTION: The relief hologram type original plate is cut to a prescribed shape and the parts to be cut are by a milling machine to grind off the ruggedness of the parts to be cut and to smooth these part so as not to generate the spacings and grooves when the parts to be cut are joined. Such original plates 1 are arrayed on a base material 2 for installation in such a manner that the smoothed parts to be cut are closely mated with each other. The installing base material 2 and the original plates 1 are placed on a surface plate 5 installed on the lower plate surface of a press machine and a backing base material 4 is superposed thereon via solder 3. Pressing under heating is executed via a heat resistant silicone rubber sheet 6 having a high thermal conductivity to join the lining base material 4 and the plural original plates 1. The installing base material 2 is then peeled and the practicable plates are produced by Ni plating.



LEGAL STATUS [Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office